SIEMENS

Data sheet 3TX7402-3R

Surge suppressor RC element with cable spacer 24-48 V AC / 24-70 V DC for mounting to coil terminal for contactors size S0-S2



General technical data		
product designation		surge suppressor
design of the surge suppressor		RC element
ambient temperature		
● during storage	°C	-40 ... +80
● during operation	°C	-25 ... +55
Control circuit/ Control		
type of voltage of the control supply voltage		AC/DC
control supply voltage frequency		
● 1 rated value	Hz	50
● 2 rated value	Hz	60
control supply voltage 1		
● at DC	V	24 ... 70
● at AC		
— at 50 Hz	V	24 ... 48
— at 60 Hz	V	48 ... 24
Certificates/ approvals		
certificate of suitability		CE / UL / CSA

General Product Approval	Declaration of Conformity

other

Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7402-3R
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7402-3R

Subject to change without notice
© Copyright Siemens

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3R
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7402-3R&lang=en

last modified: 10/22/2022

Subject to change without notice
© Copyright Siemens