PLINTEN, MSVS



Met de sokkel kan zonder enige beperking bekabeling worden aangebracht. Kabels installeren wordt eenvoudig, omdat de sokkel zorgt voor extra ruimte onder de behuizing.

KENMERKEN

Omschrijving: De vier U-vormige stukken worden met schroeven aan de hoekstukken bevestigd. Plinthoogte 100 mm. Machinale bewerking is nodig.

Materiaal: 2 mm AISI 304 / AISI 316L éénrichting geschuurd roestvaststaal.

Afwerking: 400 éénrichting geschuurd roestvaststaal.

Verpakkingseenheid: 1 plint met montagemateriaal.

SPECIFICATIES

Afwerking: Opgepoetst

Kleur: n/a

Table 1/1

Catalogusnummer	Article Number	Hoogte	Breedte	Diepte	Materiaal	Dikte
MSVS1103	MSVS1103	100 mm	1000 mm	273 mm	Roestvaststaal	2 mm
MSVS1103-316	MSVS1103-316	100 mm	1000 mm	273 mm	Roestvaststaal	2 mm
MSVS1123	MSVS1123	100 mm	1200 mm	273 mm	Roestvaststaal	2 mm
MSVS1123-316	MSVS1123-316	100 mm	1200 mm	273 mm	Roestvaststaal	2 mm
MSVS1124	MSVS1124	100 mm	1200 mm	373 mm	Roestvaststaal	2 mm
MSVS1124-316	MSVS1124-316	100 mm	1200 mm	373 mm	Roestvaststaal	2 mm
MSVS1063	MSVS1063	100 mm	600 mm	273 mm	Roestvaststaal	2 mm
MSVS1063-316	MSVS1063-316	100 mm	600 mm	273 mm	Roestvaststaal	2 mm
MSVS1083	MSVS1083	100 mm	800 mm	273 mm	Roestvaststaal	2 mm
MSVS1083-316	MSVS1083-316	100 mm	800 mm	273 mm	Roestvaststaal	2 mm
MSVS1084	MSVS1084	100 mm	800 mm	373 mm	Roestvaststaal	2 mm
MSVS1084-316	MSVS1084-316	100 mm	800 mm	373 mm	Roestvaststaal	2 mm

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.