# PLINTEN, MSVS



Met de sokkel kan zonder enige beperking bekabeling worden aangebracht. Kabels installeren wordt eenvoudig, omdat de sokkel zorgt voor extra ruimte onder de behuizing.

## KENMERKEN

Omschrijving: De vier U-vormige stukken worden met schroeven aan de hoekstukken bevestigd. Plinthoogte 100 mm. Machinale bewerking is nodig.

Materiaal: 2 mm AISI 304 / AISI 316L éénrichting geschuurd roestvaststaal.

Afwerking: 400 éénrichting geschuurd roestvaststaal.

Verpakkingseenheid: 1 plint met montagemateriaal.

## SPECIFICATIES

**Afwerking:** Opgepoetst

**Kleur:** n/a

Table 1/1

| Catalogusnummer | Article Number | Hoogte | Breedte | Diepte | Materiaal | Dikte |
|---|---|---|---|---|---|---|
| MSVS1103 | MSVS1103 | 100 mm | 1000 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1103-316 | MSVS1103-316 | 100 mm | 1000 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1123 | MSVS1123 | 100 mm | 1200 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1123-316 | MSVS1123-316 | 100 mm | 1200 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1124 | MSVS1124 | 100 mm | 1200 mm | 373 mm | Roestvaststaal | 2 mm |
| MSVS1124-316 | MSVS1124-316 | 100 mm | 1200 mm | 373 mm | Roestvaststaal | 2 mm |
| MSVS1063 | MSVS1063 | 100 mm | 600 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1063-316 | MSVS1063-316 | 100 mm | 600 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1083 | MSVS1083 | 100 mm | 800 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1083-316 | MSVS1083-316 | 100 mm | 800 mm | 273 mm | Roestvaststaal | 2 mm |
| MSVS1084 | MSVS1084 | 100 mm | 800 mm | 373 mm | Roestvaststaal | 2 mm |
| MSVS1084-316 | MSVS1084-316 | 100 mm | 800 mm | 373 mm | Roestvaststaal | 2 mm |



© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.