
ABS KLEMMENKAST GROOT, OABP



Deze reeks ABS-klemmenkasten, OABP, met beschermingsgraad IP 66/67, is in de diepte uitbreidbaar. De reeks is uit voorraad leverbaar in veel verschillende maten. Met behulp van een uitbreidingsframe, OPCP-EE, kunnen diepliggendere onderdelen worden geïnstalleerd. De OABP-reeks is zeer geschikt voor veeleisende omgevingen omdat water en stof de klemmenkast niet kunnen binnendringen, waardoor het risico op schade aan componenten en daarmee onnodige uitvaltijd wordt geëlimineerd.

KENMERKEN

Omschrijving: ABS behuizing, halogeenvrij, geschikt voor binnenopstelling. Minder goed bestand tegen UV stralen.
Materiaal: Body: ABS. Standaard deksel: ABS. Transparante kap: Polycarbonaat.
Pakking: Polyurethaanpakking (PUR), geïntegreerd in de deksel.
Temperatuurbestendigheid: -40°C tot +60°C.
Ontvlambaarheid: UL94 HB.
Beschermingsklasse: IP 66/67 | IK 06 (-25°C), IK 07 (+35°C).
Afwerking: RAL 7035.
Levering: Kastbody, deksel, dekselschroeven van polyamide en montageschroeven.
The installed components inside the terminal box will be safe and secure due to the high protection degree
Customers can receive terminal boxes with a short delivery time, that match their size requirements
This will also remove any extra costs due to oversizing
Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the terminal box
If necessary, deeper components can be installed when the expansion frame, OPCP-EE, has been mounted
The mounting plate, OMP, and DIN profiles, DR, have to be ordered separately, in order to complete the installation of the terminal box
The expansion frame, OPCP-EE, should be ordered if a deeper terminal box is required
Inner depth (mm): 115

SPECIFICATIES

Table 1/1

Catalogusnummer	Hoogte	Breedte	Diepte	Materiaal	Finish	Kleur
OABP202013GE	200 mm	200 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP202013TE	200 mm	200 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP203013GE	200 mm	300 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP203013TE	200 mm	300 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP204013GE	200 mm	400 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP204013TE	200 mm	400 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP303013GE	300 mm	300 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP303013TE	300 mm	300 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP304013GE	300 mm	400 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP304013TE	300 mm	400 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP306013GE	300 mm	600 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP306013TE	300 mm	600 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP406013GE	400 mm	600 mm	132 mm	ABS	Smooth	Lichtgrijs
OABP406013TE	400 mm	600 mm	132 mm	ABS	Smooth	Lichtgrijs

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.