EENVOUDIGE BESCHERMING VOOR KABELINVOER | WANDMONTAGE KASTEN, CES

De rubberen kabelwartel is eenvoudig te monteren en de kabels en leidingen kunnen eenvoudig zonder gereedschap in een hoek worden doorgetrokken, waardoor de beschermingsgraad van de behuizing wordt gehandhaafd.

KENMERKEN

Omschrijving: Eenvoudige tule gefabriceerd in een rubberachtig materiaal. De installatie vereist geen gereedschap. Het "pushout" membraam is een permanente afdichting tot het moment van invoer van een kabel of leiding. Je hebt altijd een ronde opening en een gewaarborgde IP. Hij is uitgerust met een sok die strak rond de kabel sluit en maakt het mogelijk om in de opening te worden verplaatst als een "joy-stick" zonder gevaar voor de IP waarde. Uitermate geschikt voor kabels die in een hoek aangebracht worden. Geschikt voor gaten in materialen van 0.5 tot 4.5 mm dik.

Materiaal: TPE (thermoplastisch rubber), halogeen vrij.

Temperatuurbestendigheid: -50 ºC tot +125 ºC.

Afwerking: RAL 7035.

Beschermingsklasse: IP 67.

The installation does not require tools

The “pushout” membrane is a permanent seal until it is penetrated by a cable or pipe

It is equipped with a sock that closes tight around the cable and allows for it to be moved around like a “joy-stick” in the opening without endangering the IP, so it works extremely well with cables passing through at an angle

Suitable for holes in materials of 0.5 to 4.5 mm thickness

Temperature resistance: -50 ºC to +125 ºC

SPECIFICATIES

Table 1/1						
Catalogusnummer	**Height (H)**	**Width (W)**	**Depth (D)**	**Materiaal**	**Finish**	**Kleur**
CES16	11 mm	24 mm	24 mm	Thermoplastisch rubber	Smooth	Lichtgrijs
CES20	11 mm	28 mm	28 mm	Thermoplastisch rubber	Smooth	Lichtgrijs
CES25	11 mm	33 mm	33 mm	Thermoplastisch rubber	Smooth	Lichtgrijs
CES32	11 mm	40 mm	40 mm	Thermoplastisch rubber	Smooth	Lichtgrijs

DIAGRAMS



© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.