GLAZEN DEUREN, ADCS

De elektrische componenten kunnen worden bekeken terwijl de deur gesloten is. Deze zorgt ervoor dat onbevoegde personen geen toegang hebben en dat de bescherming tegen binnendringing van stof en vocht wordt gehandhaafd.

KENMERKEN

Omschrijving: Ter vervanging van de standaard deur, geeft goed zicht op de gemonteerde apparatuur in de kast. Alle opties uit het slotenprogramma zijn mogelijk.

Materiaal: 1.5 mm AISI 304 roestvaststaal, 2 mm voor behuizingen met een hoogte of breedte van 600 mm of meer en 4 mm helder veiligheidsglas.

Afwerking: 400 éénrichting geschuurd roestvaststaal.

Beschermingsklasse: Overeenkomstig IP 55 | TYPE 12, 13, IK 07.

Verpakkingseenheid: 1 deur.

Glazed enclosure door for stainless steel wall mounted enclosures

The glazed door allows the electrical components to be seen while the enclosure's door is closed

The user can monitor the status of the components without the need for opening the enclosure's door maintaining the ingress protection

Note: * 3 point espagnolette locking. Not suitable for AFS

SPECIFICATIES

Table 1/1

Catalogusnummer	Hoogte	Breedte	Materiaal	Finish	Kleur	Dikte
ADCS03624	360 mm	240 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS04030	400 mm	300 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS04040	400 mm	400 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS04060	400 mm	600 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS05040	500 mm	400 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS05050	500 mm	500 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS06040	600 mm	400 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS06060	600 mm	600 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS06080	600 mm	800 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS08060	800 mm	600 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS08080	800 mm	800 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS10080	1000 mm	800 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS12080	1200 mm	800 mm	Roestvaststaal	Brushed	n/a	1.5 mm
ADCS14080	1400 mm	800 mm	Roestvaststaal	Brushed	n/a	1.5 mm

ADDITIONAL PRODUCT DETAILS

* driepunts-espagnoletsluiting. Niet geschikt voor AFS.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.