# GLAZEN DEUREN, ADCS



De elektrische componenten kunnen worden bekeken terwijl de deur gesloten is. Deze zorgt ervoor dat onbevoegde personen geen toegang hebben en dat de bescherming tegen binnendringing van stof en vocht wordt gehandhaafd.

## KENMERKEN

Omschrijving: Ter vervanging van de standaard deur, geeft goed zicht op de gemonteerde apparatuur in de kast. Alle opties uit het slotenprogramma zijn mogelijk.

Materiaal: 1.5 mm AISI 304 roestvaststaal, 2 mm voor behuizingen met een hoogte of breedte van 600 mm of meer en 4 mm helder veiligheidsglas.

Afwerking: 400 éénrichting geschuurd roestvaststaal.

Beschermingsklasse: Overeenkomstig IP 55 | TYPE 12, 13, IK 07.

Verpakkingseenheid: 1 deur.

Glazed enclosure door for stainless steel wall mounted enclosures

The glazed door allows the electrical components to be seen while the enclosure's door is closed

The user can monitor the status of the components without the need for opening the enclosure's door maintaining the ingress protection

Note: * 3 point espagnolette locking. Not suitable for AFS

## SPECIFICATIES

Table 1/1

| Catalogusnummer | Hoogte | Breedte | Materiaal | Finish | Kleur | Dikte |
|---|---|---|---|---|---|---|
| ADCS03624 | 360 mm | 240 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS04030 | 400 mm | 300 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS04040 | 400 mm | 400 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS04060 | 400 mm | 600 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS05040 | 500 mm | 400 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS05050 | 500 mm | 500 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS06040 | 600 mm | 400 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS06060 | 600 mm | 600 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS06080 | 600 mm | 800 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS08060 | 800 mm | 600 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS08080 | 800 mm | 800 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS10080 | 1000 mm | 800 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS12080 | 1200 mm | 800 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |
| ADCS14080 | 1400 mm | 800 mm | Roestvaststaal | Brushed | n/a | 1.5 mm |

## ADDITIONAL PRODUCT DETAILS

* driepunts-espagnoletsluiting. Niet geschikt voor AFS.


© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.