EMC UITLAATFILTER, EFAE



Dit verticale EMC-uitblaasfilter, EFAE, met beschermingsgraad IP 54, is gemakkelijk te installeren dankzij de inklik-functie. Water en stof kunnen de behuizing niet binnendringen via het filter, waardoor onnodige uitvaltijd wordt geëlimineerd. Met dit filter zijn de EMC-prestaties van een EMC-behuizing gewaarborgd.

KENMERKEN

Omschrijving: Speciaal geschikt voor EMC kasten. Rand van uitsnede moet blank metaal zijn voor goed contact!.
Materiaal: Plastic, UL94-V0. EMC venster: roestvast staal, contact profielen.
Goedkeuringen: CE, GOST, UR, cUL.
Beschermingsklasse: Standaard IP 54.
Verpakkingseenheid: 1 filter met behuizing.
The click-in feature ensures that the filter fan is easy to install
EMC performance is maintained when installed on an EMC enclosure
Component failure and unnecessary downtime is avoided as water, dust and electromagnetic interferences are prevented from entering the enclosure
The click-in feature reduces the customer's labour cost due to the ease of installation
To guarantee natural ventilation, install at least two exhaust filters
Forced ventilation can be achieved by adding filter fans, EFE
Filtration efficiency (%): >90
Filter mat (EN779): EFAE200R5, EFAE220R5, EFAE250-300R5: G4; EFAE500-700R5: G3

SPECIFICATIES

Table 1/1

Catalogusnummer	Hoogte	Breedte	Diepte	Materiaal	Finish	Kleur
EFAE200R5	126.5 mm	126.5 mm	26 mm	Polyamide	Polished	n/a
EFAE220R5	178 mm	178 mm	34 mm	Polyamide	Polished	n/a
EFAE250-300R5	224 mm	224 mm	38 mm	Polyamide	Polished	n/a
EFAE500-700R5	292 mm	292 mm	39 mm	Polyamide	Polished	n/a

ADDITIONAL PRODUCT DETAILS

IP 55 op aanvraag.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.