POLYCARBONAAT KLEMMENKAST GROOT, OPCP

Deze reeks polycarbonaat klemmenkasten, OPCP, met beschermingsgraad IP 66/67, is in de diepte uitbreidbaar. De reeks is uit voorraad leverbaar in veel verschillende maten. Met behulp van een uitbreidingsframe, OPCP-EE, kunnen diepliggendere onderdelen worden geïnstalleerd. De OPCP-reeks is geschikt voor binnen- en buitenomgevingen, zelfs op locaties met direct zonlicht dankzij de weerstand tegen UV-straling. Water en stof kunnen de klemmenkast niet binnendringen, waardoor het risico op schade aan componenten en daarmee onnodige uitvaltijd wordt geëlimineerd.

KENMERKEN

Omschrijving: Polycarbonaat kast, halogeenvrij, geschikt voor buitenopstelling. Hoge bestendigheid tegen UV stralen. Zelfdovend.

Materiaal: Polycarbonaat.

Pakking: Polyurethaanpakking (PUR), geïntegreerd in de deksel.

Temperatuurbestendigheid: -40 °C tot +80 °C.

Ontvlambaarheid: UL746C 5V.

Beschermingsklasse: IP 66, 67 | IK 08 (-25 °C … +35 °C).

Afwerking: RAL 7035.

Goedkeuringen: CE, GOST. Voor cULus_UL Listed goedkeuringen, neem contact op met onze verkoopafdeling.

Levering: Kastbody, deksel, dekselschroeven van polyamide en montageschroeven.

Customers can receive terminal boxes with a short delivery time, that match their size requirements which can be installed in both indoor and outdoor environments, even in locations where there is direct sunlight

This will also remove any extra costs due to oversizing

Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the terminal box

If necessary, deeper components can be installed when the expansion frame, OPCP-EE, has been mounted

The mounting plate, OMP, and DIN profiles, DR, have to be ordered separately, in order to complete the installation of the terminal box

The expansion frame, OPCP-EE, should be ordered if a deeper terminal box is required

Inner depth (mm): 115

SPECIFICATIES

Table 1/1						
Catalogusnummer	**Height (H)**	**Width (W)**	**Depth (D)**	**Materiaal**	**Finish**	**Kleur**
OPCP202013GE	200 mm	200 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP202013TE	200 mm	200 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP203013GE	200 mm	300 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP203013TE	200 mm	300 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP204013GE	200 mm	400 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP204013TE	200 mm	400 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP304013TE	300 mm	400 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP303013TE	300 mm	300 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP303013GE	300 mm	300 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP304013GE	300 mm	400 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP306013TE	300 mm	600 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP306013GE	300 mm	600 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP406013GE	400 mm	600 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs
OPCP406013TE	400 mm	600 mm	132 mm	Polycarbonaat	Smooth	Lichtgrijs

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.