VOLLEDIG DICHTE AFDEKPLAAT, UFCP



Dit is een dichte polyester voorklep, die eenvoudig machinaal kan worden bewerkt. De elektrische aansluitingen en kabels zijn afgeschermd, wat betekent dat werkzaamheden ter plaatse veilig kunnen worden uitgevoerd.

KENMERKEN

Omschrijving: Standaard afdekplaat aan de voorzijde ter bescherming van de apparatuur die in de behuizing is gemonteerd. Afstand tussen UFCP en kastdeur: 39 mm; 49 mm voor UCP750 en hoger. Omkeerbare montagepositie, om de afstand tussen UFCP en kastdeur met 30 mm te vergroten. De afdekplaat kan worden gescharnierd met het UHS-accessoire, zodat de gebruiker toegang heeft tot componenten en/of kabelbeheer zonder de afdekplaat te hoeven verwijderen.

Materiaal: Polyester.

Afwerking: RAL 7035.

Levering: Afdekplaat, steunbeugels, kwartdraai sluitingen en bevestigingsmateriaal.

SPECIFICATIES

Table 1/1

Catalogusnummer	Hoogte	Breedte	Diepte	Materiaal	Finish	Kleur
UFCP1080	1035 mm	835 mm	37 mm	Polyester	Smooth	Lichtgrijs
UFCP3200	315 mm	215 mm	37 mm	Polyester	Smooth	Lichtgrijs
UFCP4300	415 mm	315 mm	37 mm	Polyester	Smooth	Lichtgrijs
UFCP5400	515 mm	415 mm	37 mm	Polyester	Smooth	Lichtgrijs
UFCP6400	615 mm	415 mm	37 mm	Polyester	Smooth	Lichtgrijs
UFCP7500	735 mm	535 mm	37 mm	Polyester	Smooth	Lichtgrijs
UFCP8600	835 mm	635 mm	37 mm	Polyester	Smooth	Lichtgrijs

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.