# BINNENWERKEN, ALIS



Een flexibele oplossing die de mogelijkheid biedt tot verschillende vergrendelopties om de toegang tot de behuizing te beperken.

## KENMERKEN

Omschrijving: Binnenwerk ter vervanging van het standaard dubbelbaard 3 mm binnenwerk in het standaard ALLS503 slot.

Materiaal: Zamak verchroomd.

Verpakkingseenheid: Per stuk.

## SPECIFICATIES

Table 1/1

| Catalogusnummer | Article Number | Hoogte | Breedte | Diepte | Materiaal | Afwerking |
|---|---|---|---|---|---|---|
| ALIS528 | ALIS528 | 16 mm | 16 mm | 25 mm | Zamak verchroomd | Chrome Plated |
| ALIS503 | | | | | Zamak verchroomd | Chrome Plated |
| ALIS505 | | | | | Zamak verchroomd | Chrome Plated |
| ALIS523 | | | | | Zamak verchroomd | Chrome Plated |
| ALIS524 | | | | | Zamak verchroomd | Chrome Plated |
| ALIS525 | | | | | Zamak verchroomd | Chrome Plated |

## ADDITIONAL PRODUCT DETAILS

Niet geschikt voor AFS.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.