
BINNENDEUR, UID



Displays en indicatoren kunnen worden gemonteerd op een oppervlak in de behuizing, terwijl ze andere componenten afdekken en zo ongeautoriseerde toegang voorkomen.

KENMERKEN

Omschrijving: Voor schakelaars, meters, lampen, etcetera. Scharnieren kunnen gemonteerd worden, rechts- of linksdraaiend. Deur voorzien van 3 mm DIN slot.Afstand tussen UID en kastdeur: 48mm.

Materiaal: Glasvezel versterkt polyester.

Afwerking: RAL 7035.

Beschermingsklasse: IP 20.

Levering: Per stuk, inclusief bevestigingsmateriaal.

A plain door to be mounted inside a wall mounted enclosure

Additional mounting surface providing two levels of access

Non authorized personnel have access to the controls on the inner door only

This accessory is often used in enclosures with glazed door

SPECIFICATIES

Table 1/1

Catalogusnummer	Hoogte	Breedte	Materiaal	Finish	Kleur	Color Code
UID5050	500 mm	500 mm	Polyester	Smooth Matte	Lichtgrijs	RAL 7035
UID5075	500 mm	750 mm	Polyester	Smooth Matte	Lichtgrijs	RAL 7035
UID10050	1000 mm	500 mm	Polyester	Smooth Matte	Lichtgrijs	RAL 7035
UID7550	750 mm	500 mm	Polyester	Smooth Matte	Lichtgrijs	RAL 7035
UID7575	750 mm	750 mm	Polyester	Smooth Matte	Lichtgrijs	RAL 7035
UID10075	1000 mm	750 mm	Polyester	Smooth Matte	Lichtgrijs	RAL 7035

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.