# VENTILATORVERWARMING, EGL



Deze ventilatorverwarming, EGL, gebruikt een ventilator om de warmte gelijkmatig over de behuizing te verdelen, waardoor hete plekken worden voorkomen. Watercondensatie wordt geëlimineerd, ook bij sterke daling van de omgevingstemperatuur.

## KENMERKEN

Omschrijving: Verwarming inclusief ventilator

Verwarmings element: PTC weerstand, zelfregelend en beveiligd tegen oververhitting.

Levensduur: 50.000 h bij 25 °C.

Materiaal: Kunststof en geanodiseerd aluminium profiel.

Bedrijfstemperatuur: -40 °C tot +70 °C. De verwarmingscapaciteit is voor een omgevingstemperatuur van 20 °C.

Aansluiting: Terminal aansluitklem (2 × 0,5 - 2,5mm²).

Beschermingsklasse: IP 20, klasse I (geaard).

Goedkeuringen: CE

Verpakkingseenheid: Per stuk.

When installed, water condensation will be avoided especially in situations when the ambient temperature dramatically drops

As the air will be distributed by the integrated fan, hot spots within the enclosure will be prevented

A thermostat with a normally closed contact, ETR or EFR, is recommended in order to control the heater

Voltage (V): EGL250UL115, EGL400UL115 - 120 V AC, 50/60 Hz; EGL250UL230, EGL400UL230 - 230 V AC, 50/60 Hz

Protection: IP 20, Class I (earthed)

## SPECIFICATIES

Table 1/1

| Catalogusnummer | Hoogte | Breedte | Diepte | Materiaal | Finish | Kleur |
|---|---|---|---|---|---|---|
| EGL250UL230 | 187 mm | 85 mm | 104 mm | Aluminum, Polyamide | Mill | n/a |
| EGL250UL115 | 187 mm | 85 mm | 104 mm | Aluminum, Polyamide | Mill | n/a |
| EGL400UL115 | 227 mm | 85 mm | 104 mm | Aluminum, Polyamide | Mill | n/a |
| EGL400UL230 | 227 mm | 85 mm | 104 mm | Aluminum, Polyamide | Mill | n/a |



© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.