VERTICAAL SCHEIDINGSPROFIEL | VLOERSTAANDE KASTEN, VB



Het verticale scheidingsprofiel vergroot de beschikbare montagemogelijkheden binnen de behuizing, en verdeelt deze in twee bruikbare ruimtes.

KENMERKEN

Omschrijving: Gemonteerd in het midden van een 1200 of 1600mm brede behuizing. Voorziet in standaard montage faciliteiten die in twee verticale secties van 600 of 800mm. Dit geeft de mogelijkheid voor separate montage van accessoires zoals zwenkramen, systeemprofielen etc. in elke sectie van de behuizing.

Materiaal: 1.75 mm verzinkt plaatstaal.

Verpakkingseenheid: 2 stuks (excl. montagemateriaal).

Montagevoorschriften: Gebruik VBK voor montage in de behuizing. Voor volledige scheiding gebruik VBD.

Fitted in the centre of 1200 mm or 1600 mm wide enclosures (front and rear) to provide standard mounting facilities in two vertical sections of 600 mm or 800 mm

This enables separate fitting of equipment such as swing frames, system profiles, in either section of the enclosure

Pack quantity: 1 pair without mounting accessories

Mounting requirements: Add VBK for mounting. For complete mounting facilities in the division add VBD

SPECIFICATIES

Table 1/1

Catalogusnummer	Hoogte	Breedte	Diepte	Materiaal	Finish	Kleur
VB1800	1800 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a
VB2000	2000 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a
VB2200	2200 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a
VB1600	1600 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a
VB1600D	1600 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a
VB1800D	1800 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a
VB2000D	2000 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a
VB2200D	2200 mm	90 mm	24 mm	Verzinkt plaatstaal	Plated	n/a

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.