LED Driver TRIAC 150W 24V - TD-150-24-E1M1 2840900



General

Product Type	Constant Voltage Driver
Length (mm)	273
Width (mm)	57
Height (mm)	37
Housing Color	White
Housing Material	Metal
Mounting	Surface mounted
Weight (g)	790
Wire Strip Length	5mm
Wire Type	2.5mm2

Electronics

Input Domain	AC
Input Voltage	200 ~ 240V AC
Output Voltage	24V DC
Output Current Max. (A)	6.25
Output Power Range (W)	0~150
Power Factor at Full Load	+0.95 @ 230VAC
Power Supply	Internal
LED Outputs	1
Input Frequency	60Hz
Inrush Current	60A @ 230VAC

Lighting

Color Range	Single Color

Control

Output Signal	PWM-CV
Control	TRIAC
Dimming Range	0~100%
Dimming Curve	Linear
Driver Configuration	Software
Number of Channels	1

Protection

Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes

Environmental

Operating Temperature	-30 ~ +60 °C
Ingress Protection	IP20

CE IP20 2 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

OneEightyOne Valschermkade 27 - 28 | 1059CD | Amsterdam
+31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com

©2021

oneeighty one.com

Paper size: A4