LED Driver TRIAC 350-700mA 10W - TD-10-350-700-E

Referencecode: 2840700



General

Product Type	Constant Current Driver
Length (mm)	135
Width (mm)	30
Height (mm)	20
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	85
Wire Strip Length	5mm
Wire Type	2.5mm2

Electronics

Input Domain	AC
Input Voltage	200 ~ 240V AC
Output Voltage	3 ~ 14V DC
Output Current (mA) max/output	350~700
Output Power Range (W)	2.1~9.8
Power Supply	Internal
LED Outputs	1
Input Frequency	60Hz
Inrush Current	20A @ 230VAC

Lighting

Color Range	Single Color

Control

Output Signal	PWM-CC
Control	TRIAC
Dimming Range	0~100%
Dimming Curve	Linear
Number of Channels	1

Protection

Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes
Protection Class	II

Environmental

Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP20

CE IP20

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.