



Ever DALI 500-1750mA 50W - DALI-50-500-1750 28205 Datasheet

Technical Specs

General	
Product Type	Constant Current Driver
Length (mm)	133
Width (mm)	89
Height (mm)	30
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	320
Electronics	
Input Domain	AC
Input Voltage	100 ~ 240V AC
Output Voltage	10 ~ 54V DC
LED Output Current (max per o	500~1750
Output Power Range (W)	5~51
Power Supply	Internal
LED Outputs	1
Input Frequency	50Hz, 60Hz
Inrush Current	10A @ 230VAC
Lighting	
Color Range	Single Color
Control	
Output Signal	PWM-CC
Control	DALI
Push Dim	yes
Dimming Range	0~100%
Dimming Curve	Logaritmik
Driver Configuration	Dip Switches
Number of Channels	1
Protection	
Reverse Polarity	Yes
Protection Class	II
Environmental	
Operating Temperature	-30 ~ 55 °C
Ingress Protection	IP20
Environment	Indoor
-	
ETIM Classification	EC002710 LED Driver
HS Code	8504318050

Regulations

Approvals	
CE	✓



Order information

Code	Description
28205	LED Driver DALI 500-1750mA 50W - DALI-50-500-1750-F1P1

