LED Decoder DMX 4x6A - LT-840-6A

Referencecode: 2270400



General

Product Type	Constant Voltage Driver
Length (mm)	156
Width (mm)	78
Height (mm)	40
Housing Color	Matte Black
Housing Material	Metal
Mounting	Surface mounted
Weight (g)	435
Wire Strip Length	5mm
Wire Type	2.5mm2

Electronics

Input Domain	DC
Input Voltage	5 ~ 24V DC
Output Voltage	5 ~ 24 V DC
Output Current (mA) max/output	6000
Output Current Max. (A)	24
Output Power (W)	120W @ 5V, 288W @ 12V, 576W @ 24V
Power Supply	N/A
LED Outputs	4

Lighting

Color Range	RGBW

Control

Output Signal	PWM-CV
Control	DMX
RDM Support	Yes
Dimming Range	0~100%
Dimming Curve	Linear
Driver Configuration	Dip Switches
Number of Channels	4

Wiring

DMX Socket	RJ45, XLR-3, Screw Terminal

Protection

Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes

Environmental

Operating Temperature	-30 ~ +65 °C
Ingress Protection	IP20

CE FC IP20

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.

©2022