ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: LAVA2-GLAS-800-MR
Art. Nr.: 39654

0 912006 139118

Short description

Infrared heating panel, glass, mirror, 160x50cm, 800W, 230V

Product Description

LAVA 2.0 design infrared heating panels work particularly efficiently and save energy. The 6 mm thick surface material made of safety glass, special ceramic or fine stone, as well as 2 temperature limiters in all panels ensure safety at all times. The innovative technology makes the surfaces a very good radiation emitter. In combination with the even heat distribution on the surface, the optimally insulated back surface guarantees a high radiation efficiency and thus maximum infrared heat radiation to the front into the room. The frame-less design is modern. There are four surfaces (STEEL/GLASS/CERAMIC/STONE) and up to 6 power settings to choose from. The practical Plug & Play box at the back of all LAVA 2.0 models allows easy installation of a control, whether directly on the unit, by radio or by means of a wired controller. With LAVA DYL 2.0 - Design Your LAVA - it is possible to apply your own designs, pictures and photos on the LAVA GLAS 2.0 or LAVA BATH 2.0. On/off switch, surface temperature: max. 95 °C, vertical and horizontal wall mount possible, protection rating: IP X4, surfaces: sheet steel, 6 mm toughened safety glass, 6 mm special ceramic or 6 mm fine stone, plug connection cable: 1 m, certification mark: TÜV, CE marking.

ETIM characteristics

Type of IR radiation	IR-C
Mounting method	Surface mounting
Mounting direction	Horizontal/vertical
Degree of protection (IP)	IPX4
Colour	Other
With imprint	✖
With room temperature controller	✖
With mounting material	✔
With framework	✖
Material framework	Other
Colour framework	Other
Surface treatment	Other
Surface structure front-side panel	Mirror
With lighting cove	✖
Dimmable	✖
Light outlet	Direct

Power consumption	800 Watt
Supply voltage	230|230 Volt
Frequency supply voltage	50|50 Hertz
Max. surface temperature	95 Degrees celsius
Height	500 Millimetre
Width	1600 Millimetre
Depth	61 Millimetre
RAL-number	0

Created on: 27/11/2023