ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: LAVALITE-GL-240-PW
Art. Nr.: 40903

0 912010 541076

Short description

Infrared heating panel thin, glass, pure white, 50x63cm, 240W, 230V

Product Description

The extra thin LAVA LITE infrared heating panel is impressive with its efficiency. Despite the 6 mm thick safety glass, the infrared heating panel is only 33 mm deep, including the mounting rails, making it ideal for wall mounting - even where there is less space, such as in hallways or stairwells. The glass surface is a very good radiation emitter and ensures optimal heat radiation. Due to the frame-less design and extremely shallow depth, the infrared heating panel blends harmoniously with the room. The glass surface is available in pure white and mirror finish. Outputs: 240, 450, 700 and 900 W, mounting depth: 33 mm, surface temperature: approx. 95 °C, vertical and horizontal wall mounting possible, protection rating: IP X4, surfaces: 6 mm ESG safety glass, plug connection cable: 1 m, CE marking.

ETIM characteristics

Type of IR radiation	IR-C
Mounting method	Surface mounting
Mounting direction	Horizontal/vertical
Degree of protection (IP)	IP55
Colour	White
With imprint	✖
With room temperature controller	✖
With mounting material	✔
With framework	✖
Material framework	Other
Colour framework	Other
Surface treatment	Other
Surface structure front-side panel	Smooth
With lighting cove	✖
Dimmable	✖
Light outlet	Direct

Power consumption	240	Watt
Supply voltage	230|230	Volt
Frequency supply voltage	50|50	Hertz
Max. surface temperature	95	Degrees celsius
Height	630	Millimetre
Width	500	Millimetre
Depth	33	Millimetre
RAL-number	0	

Created on: 27/11/2023

ETHERMA Elektrowärme GmbH
Landesstrasse 16
A-5302 Henndorf am Wallersee
Tel.: +43 6214 / 76 77
Mail: office@etherma.com
Web: www.etherma.com

ETHERMA Deutschland GmbH
Bahnhofstraße 40
D-48599 Gronau
Tel.: +49 2562 / 81 97 00
Mail: office.de@etherma.com
Web: www.etherma.com