ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: LAVA2-GLAS-750-PW
Art. Nr.: 39628

0 912006 139093

Short description

infrared heating panel, glass, pure white, 130x63cm, 750W, 230V

Product Description

LAVA 2.0 design infrared heating panels work particularly efficiently and save energy. The 6 mm thick surface material made of safety glass, special ceramic or fine stone, as well as 2 temperature limiters in all panels ensure safety at all times. The innovative technology makes the surfaces a very good radiation emitter. In combination with the even heat distribution on the surface, the optimally insulated back surface guarantees a high radiation efficiency and thus maximum infrared heat radiation to the front into the room. The frame-less design is modern. There are four surfaces (STEEL/GLASS/CERAMIC/STONE) and up to 6 power settings to choose from. The practical Plug & Play box at the back of all LAVA 2.0 models allows easy installation of a control, whether directly on the unit, by radio or by means of a wired controller. With LAVA DYL 2.0 - Design Your LAVA - it is possible to apply your own designs, pictures and photos on the LAVA GLAS 2.0 or LAVA BATH 2.0. On/off switch, surface temperature: max. 95 °C, vertical and horizontal wall mount possible, protection rating: IP X4, surfaces: sheet steel, 6 mm toughened safety glass, 6 mm special ceramic or 6 mm fine stone, plug connection cable: 1 m, certification mark: TÜV, CE marking.

ETIM characteristics

Type of IR radiation	IR-C	**Power consumption**	750	Watt
Mounting method	Surface mounting	**Supply voltage**	230|230	Volt
Mounting direction	Horizontal/vertical	**Frequency supply voltage**	50|50	Hertz
Degree of protection (IP)	IPX4	**Max. surface temperature**	95	Degrees celsius
Colour	White	**Height**	630	Millimetre
With imprint	✖	**Width**	1300	Millimetre
With room temperature controller	✖	**Depth**	61	Millimetre
With mounting material	✔	**RAL-number**	0	
With framework	✖			
Material framework	Other			
Colour framework	White			
Surface treatment	Other			
Surface structure front-side panel	Smooth			
With lighting cove	✖			
Dimmable	✖			
Light outlet	Direct			

Created on: 27/11/2023

ETHERMA Elektrowärme GmbH
Landesstrasse 16
A-5302 Henndorf am Wallersee
Tel.: +43 6214 / 76 77
Mail: office@etherma.com
Web: www.etherma.com

ETHERMA Deutschland GmbH
Bahnhofstraße 40
D-48599 Gronau
Tel.: +49 2562 / 81 97 00
Mail: office.de@etherma.com
Web: www.etherma.com