

PRODUCT DATASHEET

Type: eTRACE-HW-PRO
Art. Nr.: 41248

**Short description**

Self-regulating hot water heating belt, 13 W/m

*** Image not allowed:
<https://pim.compano.com/Data/Environments/000039/Attachments/PRD/PPI/41248.jpg> ***

Product Description

The self-regulating heating tape eTRACE-HW-PRO is used on containers, pipes, valves and more for temperatures between 30 °C and approx. 80 °C. The heating tape may be completely immersed in liquid, with the exception of the connections. The eTRACE-HW-PRO heating tape is often used to heat grease pipes, e.g. in the food industry. But they are also useful for wastewater pipes in canteens and (large) kitchens to prevent the deposition of grease due to heating. The heating tape is moisture-proof and UV-resistant; the supply conductors are nickel-plated copper. Self-adjusting heating tapes can be easily cut to the desired length and used immediately. Max. ambient temperature: 85 °C switched off, Nominal temperature: 65 °C switched on, min. Mounting temperature: -30°C, min. Bending radius: 25 mm, max. Heating circuit length at 0 °C/16 A: 75 m, 230V, CE marking

ETIM characteristics

Screening	Braiding	Nominal voltage	230 Volt
Colour	Black	Max. hold temperature	85 Degrees celsius
Application	Fluid temperature monitoring	Heating capacity	11 Watt per metre
		Diameter	0 Millimetre
		Height	6.1 Millimetre
		Width	13.2 Millimetre
		Length	0 Metre

Created on: 27/11/2023