


PRODUCT DATASHEET

Type: LAVA-MAX-GL-1500-PW
Art. Nr.: 46182



Short description

Ceiling infrared heater, glass, white, 62x124,5cm, 1500W, 230V



Product Description

With LAVA MAXIMUS ETHERMA presents an infrared heating with extra strong performance thanks to high surface temperature. Due to the extra power, the infrared panel is particularly suitable for high rooms and for increased heat demand. The installation is either surface mounted on the ceiling or the infrared heating is integrated into a grid ceiling. Installation in a grid ceiling is very easy thanks to the standard grid ceiling dimensions of the panel. It can be flexibly used instead of a module and provides pleasant, gentle heat from above within minutes. Ideal as a full-fledged building heating or as an additional and zone heating in offices and sales rooms, as well as for high living spaces. Infrared heaters do not heat people and objects in the room the air, so there is no unpleasant dust swirling or dry heating air. Ideal conditions for a comfortable working environment. Due to the ceiling mounting, the heat distribution is particularly efficient, and at the same time the room is optimally utilized. The surface is made of white satin glass. The frame is made of powder-coated aluminum. Available in 3 power levels (600-1500 W). Protection class: IP 24, surface temperature: approx. 180 °C, mounting depth: 55 mm, CE compliant; connection cable: 1 m, 3 x 1.5 mm² without plug and without plug & play connection. Warranty 5 years. Made in Austria. 230 V.

ETIM characteristics

Type of IR radiation	IR-C	Power consumption	1500 Watt
Mounting method	Surface mounting	Supply voltage	230 230 Volt
Mounting direction	Horizontal	Frequency supply voltage	50 50 Hertz
Suitable for ceiling mounting	✓	Max. surface temperature	180 Degrees celsius
Degree of protection (IP)	IP24	Height	620 Millimetre
Colour	White	Width	1245 Millimetre
With imprint	✗	Depth	55 Millimetre
With room temperature controller	✗	RAL-number	0
With mounting material	✓	Colour temperature	0 0 Kelvin
With framework	✓		
Material framework	Aluminium		
Colour framework	White		
Surface treatment	Other		
Surface structure front-side panel	Rough		
With lighting cove	✗		
Dimmable	✗		
Light outlet	Direct		

Created on: 27/11/2023