ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: RLH-15-17
Art. Nr.: 34441

0 912006 139482

Short description
Heating loop for screed installation, 15W/m, 17m, 259W, 230V



Product Description
The RLH heating loops are ideal for laying in concrete and flowing screeds in interior areas for temperature control of floors. The laying distance allows application-oriented laying for each room. The factory-made heating loops with 15 or 20 W/m consist of a dipole heating conductor and a non-heating connection cable (cold end) with a length of 3 m, which is permanently waterproof. For an additional charge, the connecting cable can be produced in the desired length. Temperature resistant up to 90 °C, system design: CE marking, protection rating: IP X7, protective measure: RCD circuit 30 mA, heating conductor design according to VDE NH2G2GQUY, min. bending radius: 5 d.

ETIM characteristics

Cable type	Dual core	**Nominal voltage**	230 Volt
Screening	Braiding	**Max. hold temperature**	90 Degrees celsius
Colour	Black	**Heating capacity**	15 Watt per metre
Application	Other	**Diameter**	6 Millimetre
		Height	0 Millimetre
		Width	0 Millimetre
		Length	17 Metre

Created on: 27/11/2023

ETHERMA Elektrowärme GmbH
Landesstrasse 16
A-5302 Henndorf am Wallersee
Tel.: +43 6214 / 76 77
Mail: office@etherma.com
Web: www.etherma.com

ETHERMA Deutschland GmbH
Bahnhofstraße 40
D-48599 Gronau
Tel.: +49 2562 / 81 97 00
Mail: office.de@etherma.com
Web: www.etherma.com