


PRODUCT DATASHEET

Type: LAVA-BASIC-1500DM
Art. Nr.: 39723



Short description

infrared heating panel, wall/ceiling, white, 124.5x124.5cm, 1500W



Product Description

LAVA BASIC-DM is an infrared heating panel only 22 mm deep, which is suitable for heating both the ceiling and wall and produces infrared radiant heat due to a special magnetic field-free heating element. Unlike conventional heaters, it heats not only the air, but people and objects in the room too. In addition, the devices are ideal for use as complete or zone heating. When installed in suspended ceilings, the heater is fully integrated into the ceiling. Ceiling mounting allows optimal use of space, and also prevents damage to the heater. Available in traffic white RAL 9016, nano anthracite RAL 7016 and in the LAVA BASIC-DM RAL version in all RAL colours and up to 6 power settings (350-1500 W). Fine textured surface, Body: steel housing, protection rating: IP 21, surface temperature: ceiling mount max. 120 °C/wall mount max. 95 °C, mounting depth: 52 mm, certification mark: TÜV, CE; connection cable: 1 m, 3 x 1.5 mm² without plug and without Plug & Play connection. 230 V.

ETIM characteristics

Type of IR radiation	IR-C	Power consumption	1500 Watt
Mounting method	Surface mounting	Supply voltage	230 230 Volt
Mounting direction	Horizontal/vertical	Frequency supply voltage	50 50 Hertz
Degree of protection (IP)	IP21	Max. surface temperature	120 Degrees celsius
Colour	White	Height	1245 Millimetre
With imprint	×	Width	1245 Millimetre
With room temperature controller	×	Depth	52 Millimetre
With mounting material	✓	RAL-number	9016
With framework	×		
Material framework	Other		
Colour framework	White		
Surface treatment	Other		
Surface structure front-side panel	Smooth		
With lighting cove	×		
Dimmable	×		
Light outlet	Direct		

Created on: 27/11/2023