

## PRODUCT DATASHEET

**Type:** ET-SET-EEZ8-RF  
**Art. Nr.:** 46460



### Short description

Workplace heating set 1-2 persons incl. wireless control



### Product Description

The ETHERMA workplace heating set consists of 2 pieces 800W infrared heating and a wireless thermostat with wireless relay which is pre-wired. This workplace heating set is ideally suited for workplaces in warehouses, workshops, drafty areas or office situations with an industrial look. The workplace heating set is suitable for an area of + / - 8m<sup>2</sup>. The wireless thermostat communicates via RF with the relay. Because the relay is already pre-wired, connecting and placing is quick and easy. Total heating power is 1600W / voltage: 230V / The relay has a maximum switching capacity of 16A.

### ETIM characteristics

|                                           |                  |                                 |                     |
|-------------------------------------------|------------------|---------------------------------|---------------------|
| <b>Type of IR radiation</b>               | IR-B             | <b>Power consumption</b>        | 1600 Watt           |
| <b>Mounting method</b>                    | Surface mounting | <b>Supply voltage</b>           | 220 230 Volt        |
| <b>Mounting direction</b>                 | Horizontal       | <b>Frequency supply voltage</b> | 50 60 Hertz         |
| <b>Suitable for ceiling mounting</b>      | ✓                | <b>Max. surface temperature</b> | 340 Degrees celsius |
| <b>Degree of protection (IP)</b>          | IP44             | <b>Height</b>                   | 50 Millimetre       |
| <b>Colour</b>                             | White            | <b>Width</b>                    | 650 Millimetre      |
| <b>With imprint</b>                       | ✗                | <b>Depth</b>                    | 290 Millimetre      |
| <b>With room temperature controller</b>   | ✓                | <b>RAL-number</b>               | 9016                |
| <b>With mounting material</b>             | ✓                |                                 |                     |
| <b>With framework</b>                     | ✗                |                                 |                     |
| <b>Surface treatment</b>                  | Lacquered        |                                 |                     |
| <b>Surface structure front-side panel</b> | Other            |                                 |                     |
| <b>With lighting cove</b>                 | ✗                |                                 |                     |
| <b>Dimmable</b>                           | ✗                |                                 |                     |

Created on: 14/02/2024