

PRODUCT DATASHEET

Type: LAVALITE-GL-450-PW
Art. Nr.: 40904



Short description

Infrared heating panel thin, glass, pure white, 90x63cm, 450W, 230V



Product Description

The extra thin LAVA LITE infrared heating panel is impressive with its efficiency. Despite the 6 mm thick safety glass, the infrared heating panel is only 33 mm deep, including the mounting rails, making it ideal for wall mounting - even where there is less space, such as in hallways or stairwells. The glass surface is a very good radiation emitter and ensures optimal heat radiation. Due to the frame-less design and extremely shallow depth, the infrared heating panel blends harmoniously with the room. The glass surface is available in pure white and mirror finish. Outputs: 240, 450, 700 and 900 W, mounting depth: 33 mm, surface temperature: approx. 95 °C, vertical and horizontal wall mounting possible, protection rating: IP X4, surfaces: 6 mm ESG safety glass, plug connection cable: 1 m, CE marking.

ETIM characteristics

Type of IR radiation	IR-C	Power consumption	450 Watt
Mounting method	Surface mounting	Supply voltage	230 230 Volt
Mounting direction	Horizontal/vertical	Frequency supply voltage	50 50 Hertz
Degree of protection (IP)	IP55	Max. surface temperature	95 Degrees celsius
Colour	White	Height	630 Millimetre
With imprint	✗	Width	900 Millimetre
With room temperature controller	✗	Depth	33 Millimetre
With mounting material	✓	RAL-number	0
With framework	✗		
Material framework	Other		
Colour framework	Other		
Surface treatment	Other		
Surface structure front-side panel	Smooth		
With lighting cove	✗		
Dimmable	✗		
Light outlet	Direct		

Created on: 27/11/2023