Puncture free ANTI-PUNCTURE SEALANT

OKO©

Application chart / Tableau Des Doses D'application
Tabla De Aplication / Tabella di Applicazione / Quadro de Aplicaco

Off Road Vehicles

Ride ON Lawn Mowers, Golf Carts, Trailers, Fork Lift Trucks.
Brouettes, Chariots de Golfe, Remorques, Les Tondeuses Autoportees
Segadores Motorizadas, Carros de Golfe, Remolques, Otros.
Tabliaerba, Rimorchi, Altro, "Golf Cart"
Cortadores de Relva, Carrinhos de Golfe, Reboques.

TYRE Size. Taille du Pneu Tamano del neumatico Dim. Pneumatico Tomanho do Pneu	RIM Jante Llanta	OKO MLS
4 Inch Rims		
2.50	4	150
2.80	4	150
3.00	4	150
3.50	4	150
4.10 NHS	4	200
4.10 x 3.50	4	250
9 x 3.50	4	250
4.80 NHS	4	250
11 x 4.00	4	250
4.5 Inch Rims		
14.50	4.5	600
5 Inch Rims		
3.40 NHS	5	150
3.40 x 3.00	5	150
3.50	5	150
4.10	5	200
4.10 x 3.50	5	200
11 x 4.00	5	200
13 x 4.00	5	400
6 Inch Rims		
3.00	6	200
3.50	6	200
4.00	6	200
4.00 x 3.25	6	200
4.10 x 3.50	6	200
4.10 NHS	6	200
5.30	6	300
6.90	6	400
8.00	6	400
120 / 70	6	300
12 x 10.00	6	400
13 x 5.00	6	250
13 x 6.00	6	300
13 x 6.50	6	350
14 x 4.00	6	300
14 x 8.00 NHS	6	500
15 x 6.00	6	400
16 x 4.50	6	350
6.5 Inch Rims		
18.00	6.5	400
7 Inch Rims		
4.50	7	300
4.80	7	300
8 Inch Rims		
2.50	8	200
3.00	8	200
3.50	8	200
3.50	8	200
4.00	8	200
4.00 x 2.50	8	200
4.00 x 3.00	8	200
4.00 x 3.25	8	250
4.30	8	250
4.80 x 4.00	8	300
4.80 NHS	8	300
4.80 x 3.75	8	300
5.00	8	300
5.00 x 3.00	8	300
5.00 x 3.25	8	300
5.70 x 4.50	8	300
15 x 6.00	8	400
16 x 5.50	8	400
16 x 6.50	8	400
16 x 7.50	8	400
16.5 x 6.50	8	400
170 / 60	8	400
18 x 5.00	8	400
18 x 6.00	8	400
18 x 6.50	8	450
18 x 7.00	8	500
18 x 7.00 NHS	8	500
18 x 8.50	8	600
18 x 9.50	8	600
18 x 9.50 NHS	8	600
180 / 70	8	400
18 x 11.00	8	600
18.5 x 8.50	8	600
8 Inch Rims		
18.5 x 9.50	8	700
20 x 7.00	8	500
20 x 8.00	8	600
20 x 10.00	8	600
20 x 11.00	8	600
20 x 12.00	8	800
20.5 x 8.00	8	600
210 x A3760	8	500
21 x 7.00	8	600
21 x 11.00	8	800
21 x 12.00	8	800
22 x 11.00	8	800
22.50 x 10.00	8	800
23 x10.00-12	8	800
25 x12.00	8	800
8.5 Inch Rims		
18.00	8.5	800
9 Inch Rims		
4.00	9	250
4.80 NHS	9	300
5.50/85	9	400
6.00	9	400
6.00 x 4.00	9	500
6.90 NHS	9	500
20 x 11.00	9	600
21.20 x 7.00	9	500
21 x 8.00 NHS	9	600
21.8 x 6.00	9	600
21.9 x 7.00	9	700
21 x 9.00 NHS	9	700
21 x 11.00	9	800
21 x 12.00	9	800
23 x 10.00	9	800
25 x 12.00	9	800

NOT TO BE USED IN VEHICLES THAT EXCEED 50 M.P.H. (80 K.P.H). / A NE PAS APPLIQUER SUR DES VEHICULES ROULANT A PLUS DE 80 KPH SUR LA ROUTE
NO SER UTILIZADO EN VEHICULOS EN LA CARRETERA QUE SOBREPASAN 80 KPH. / NON UTILIZZARE SU VEICOLI STRADLI CHE SUPERANO I 80 KPH.
NAO DEVE SER USADO EM VEICULOS DE ESTRADA QUE EXCEDAM OS 80 KPH.

OKO_Offroad_01.indd 1 20/04/2010 09:29

Puncture free ANTI-PUNCTURE SEALANT

Application chart / Tableau Des Doses D'application
Tabla De Aplication / Tabella di Applicazione / Quadro de Aplicaco

Off Road Vehicles

Ride ON Lawn Mowers, Golf Carts, Trailers, Fork Lift Trucks.
Brouettes, Chariots de Golfe, Remorques, Les Tondeuses Autoportees
Segadores Motorizadas, Carros de Golfe, Remolques, Otros.
Tabliaerba, Rimorchi, Altro, "Golf Cart"
Cortadores de Relva, Carrinhos de Golfe, Reboques.

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
10 Inch Rims		
4.00	10	400
6.50	10	600
6.50 x 5.00	10	600
6.50 x 5.50	10	600
7.00 / 85	10	600
7.50 x 5.00	10	700
7.50 x 5.50	10	700
7.50 NHS	10	700
9.00 NHS	10	900
18 x 9.50	10	600
18 x 11.00	10	600
20 x 5.00	10	600
20 x 8.00 NHS	10	600
20 x 10.00	10	600
20 x 11.00	10	600
20 x 12.00	10	600
20.5 x 8.00	10	600
21. x 7.00	10	600
22 x 8.00	10	600
22 x 10.00	10	600
22 x 11.00	10	700
23.8 x 6.50	10	600
23.8 NHS	10	700
23.9 x 6.50	10	700
27 x 9.00 NHS	10	900
27 x 15.00	10	1500
12 Inch Rims		
23 x 8.5	12	700
24 x 12	12	1000
24 x 13	12	1000
27 x 13	12	1000
31 x 12.5	12	1400
3.50	12	400
4.00	12	400
4.50	12	400
4.80 NHS	12	400
5.00	12	400
5.30	12	400

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
12 Inch Rims		
5.70	12	400
6.00	12	600
6.50	12	600
6.90	12	600
7.00	12	600
7.00 x 5.00	12	700
8.00	12	600
8.50	12	700
10.00	12	700
10.00 x 75	12	700
10.00 x 80	12	700
11.00 x 65	12	800
12.00	12	800
170.00/80	12	700
210.00/65	12	800
22 x 7.50	12	600
22.00 x 8.00	12	600
23.00 x 8.00	12	700
23.00 x 8.50	12	700
23.00 x 9.00	12	700
23.00 x 9.50	12	750
23.00 x 10.00	12	800
23.00 x 10.50	12	850
23.00 x 12.00	12	900
23.5 x 8.50	12	700
24 x 12.00	12	1000
24.00 x 13.00	12	1000
26.00 x 12.00	12	1000
27.00 x 8.50	12	800
27.00 x 10.00	12	1000
27.00 x 10.50	12	1000
32.00 x 10.5	12	1000
13 Inch Rims		
6.50	13	600
6.50 x 80	13	600
A78	13	600
B78	13	600
C78	13	600

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
14 Inch Rims		
4.00	14	400
4.50	14	400
5.00	14	600
6.00	14	700
7.00	14	800
8.50	14	900
9.50	14	1000
11.00	14	1400
165	14	700
170 x 80	14	800
185	14	800
195	14	800
205	14	1000
E78	14	1200
F70	14	1200
F78	14	1400
G78	14	1400
H70	14	1400
H78	14	1400
15 Inch Rims		
4.00	15	400
5.00	15	500
5.50	15	500
5.70	15	600
5.90	15	700
6.40	15	700
6.50 x 80	15	700
6.70	15	800
7.00	15	800
7.00 x 5.50	15	800
7.00 x 6.50	15	1000
7.50 x 15	15	1000
7.50 x 5.50	15	1200

NOT TO BE USED IN VEHICLES THAT EXCEED 50 M.P.H. (80 K.P.H). / A NE PAS APPLIQUER SUR DES VEHICULES ROULANT A PLUS DE 80 KPH SUR LA ROUTE
NO SER UTILIZADO EN VEHICULOS EN LA CARRETERA QUE SOBREPASAN 80 KPH. / NON UTILIZZARE SU VEICOLI STRADLI CHE SUPERANO I 80 KPH.
NAO DEVE SER USADO EM VEICULOS DE ESTRADA QUE EXCEDAM OS 80 KPH.

OKO_Offroad_01.indd 2 20/04/2010 09:29

Puncture free ANTI-PUNCTURE SEALANT

OKO©

Application chart / Tableau Des Doses D'application
Tabla De Aplication / Tabella di Applicazione / Quadro de Aplicaco

Off Road Vehicles

Industrial, Construction, Agricultural, Tractors, Trailers, Heavy Earthmovers.
Vehicules Industriels, Agricoles, Tracteurs, Semi Remorques, Engines de Terrassment.
Industria, Agricultura, Construccion y Servicios, Tractores, Movimiento de Tierras.
Industriale, Agricolo, Trattori, Edile e Utilita, Veicolo Movimento Terra.
Industria Mineira, Agricola, Tractores, Construcao e Acessorios.

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
12 Inch Rims		
7.00	12	600
10.00	12	700
11.00 / 65	12	800
12.00	12	800
14 Inch Rims		
9.50	14	1000
11.00	14	1400
15 Inch Rims		
7.60	15	1200
7.75	15	1400
8.25	15	1600
8.50	15	1600
8.55	15	1600
9.00	15	1600
9.50	15	1600
10.00	15	1800
10.50	15	1800
10.00 x 75	15	1800
11.00	15	2000
11.50	15	2000
12.00	15	2200
12.50	15	2200
13.50	15	2400
225 x 75	15	1600
240 x 70	15	1800
25 x 7.50	15	1000
27 x 8.50	15	1000
27 x 9.50	15	1000
27 x 10.50	15	1200
28 x 9.00 NHS	15	1000
28 x 12.00 NHS	15	1400
28 x 13.00 NHS	15	1400
29 x 8.00 NHS	15	1000
29 x 12.50	15	1400
31.00 x 12.50	15	1400
31.00 x 13.50	15	1600
31.00 x 15.50	15	1800
32.00 x 12.00	15	1400

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
15 Inch Rims		
32.00 x 15.00	15	1800
32.00 x 12.10/9.75	15	1600
33.00 x 12.50	15	1800
35.00 x 15.00	15	2000
35.00 x 11 NHS	15	1600
E78	15	1400
F78	15	1600
G78	15	1800
H78	15	2000
15.3 Inch Rims		
10.00	15.3	1800
10.00 x 75	15.3	1800
10.00 x 85	15.3	1800
10.50 / 85	15.3	1800
11.50	15.3	2000
11.50 / 80	15.3	2000
10.00	15.3	2200
16 Inch Rims		
4.00	16	500
4.50	16	500
5.00	16	600
5.50	16	600
6.00	16	800
6.50	16	800
6.50 / 4.50	16	800
7.00	16	1000
7.20	16	1200
7.50	16	1200
7.50 / 5.50	16	1200
7.75	16	1400
8.00	16	1600
8.25	16	1600
8.30	16	1600
9.00	16	1600
9.50	16	1600
10.00	16	1800
10.00 / 75	16	1800
10.50 / 65	16	1800

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
16 Inch Rims		
11.00	16	2200
11.20	16	2200
11.50 / 70	16	2200
12.40	16	2400
12.50	16	2400
13.60	16	2600
13.00 / 75	16	2600
14.00 / 65	16	2800
205.00	16	1600
210 / 80	16	1600
230 / 80	16	1600
250 / 80	16	1800
9.00 / 70	16	1600
16.1 Inch Rims		
13.50	16.1	2800
14.00	16.1	3000
14.50 / 75	16.1	3200
16.50	16.1	3800
18.40	16.1	4600
19.00	16.1	4800
21.50	16.1	5600
16.5 Inch Rims		
8.00	16.5	1600
8.75	16.5	1800
9.5	16.5	1800
10.00	16.5	2000
12.00	16.5	2400
>>>>> cont'd		

NOT TO BE USED IN VEHICLES THAT EXCEED 50 M.P.H. (80 K.P.H). / A NE PAS APPLIQUER SUR DES VEHICULES ROULANT A PLUS DE 80 KPH SUR LA ROUTE
NO SER UTILIZADO EN VEHICULOS EN LA CARRETERA QUE SOBREPASAN 80 KPH. / NON UTILIZZARE SU VEICOLI STRADLI CHE SUPERANO I 80 KPH.
NAO DEVE SER USADO EM VEICULOS DE ESTRADA QUE EXCEDAM OS 80 KPH.

OKO_Offroad_01.indd 3 20/04/2010 09:29

Puncture free ANTI-PUNCTURE SEALANT

Application chart / Tableau Des Doses D'application
Tabla De Aplication / Tabella di Applicazione / Quadro de Aplicaco

Off Road Vehicles

Ride ON Lawn Mowers, Golf Carts, Trailers, Fork Lift Trucks.
Brouettes, Chariots de Golfe, Remorques, Les Tondeuses Autoportees
Segadores Motorizadas, Carros de Golfe, Remolques, Otros.
Tabliaerba, Rimorchi, Altro, "Golf Cart"
Cortadores de Relva, Carrinhos de Golfe, Reboques.

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
17 Inch Rims		
7.00	17	1400
7.50	17	1400
7.50 / 6.00	17	1600
8.25	17	1800
10.00	17	2200
12.00	17	2600
15.00 / 55	17	3200
19.00 / 45	17	4800
17 Inch Rims		
7.00	17.5	1400
8.00	17.5	1600
8R	17.5	1600
9.50	17.5	2200
10.00	17.5	2200
14.00	17.5	3200
18 Inch Rims		
4.00	18	600
7.00	18	1400
7.50	18	1600
7.50 NHS	18	1800
8.00	18	2000
8.25	18	2000
10.00	18	2200
10.50	18	2400
10.50 / 80	18	2200
11.50 / 70	18	2400
12.00	18	2800
12.50 / 80	18	2800
13.00 / 65	18	3000
14.50 / 80	18	3400
15.00 / 70	18	3400
250 / 80	18	2200
16.5 / 80	18	3800
19 Inch Rims		
4.00	19	800
4.50	19	800
5.00	19	800
6.00	19	1000

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
19 Inch Rims		
7.00	19	1400
8.00	19	1800
19R x 400	19	3400
19R	19	3300
19.5 Inch Rims		
8.00	19.5	2000
9.50	19.5	2200
10.00	19.5	2400
15.00	19.5	3800
16.50	19.5	4000
18.00	19.5	4800
19.50	19.5	5400
445 / 65	19.5	4800
20 Inch Rims		
6.00	20	1200
6.50	20	1400
7.00	20	1500
7.50	20	1600
8.00	20	1800
8.25	20	2000
8.25 / 5.50	20	2000
9.00	20	2200
9.00 / 6.50	20	2200
9.50	20	2200
10.00	20	2400
10.00 / 6.50	20	2400
10.00 / 8.00	20	2600
10.5	20	2600
20.00 x 70	20	5600
21.00 x 80	20	5600
44 x 18. NHS	20	5200
400 / 70	20	4200
21 Inch Rims		
6.00	21	1400
12.00	21	3200
14.00	21	4000
16.00	21	4800
18.00	21	5000

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
21 Inch Rims		
23.00	21	6000
22 Inch Rims		
10.00	22	2800
11.00	22	3000
12.00	22	3400
22.5 Inch Rims		
8.00	22.5	2200
9.00	22.5	2500
10.00	22.5	2800
11.00	22.5	3000
12.00	22.5	3400
12.50	22.5	3600
15.00	22.5	4400
15.50 x 70	22.5	4400
16.00	22.5	4800
16.50	22.5	5000
16.50 x 70	22.5	5000
18.00	22.5	5400
275 / 70	22.5	3000
315 / 70	22.5	3400
400 / 55	22.5	4800
500 x 60	22.5	5800
550 x 60	22.5	6000
23 Inch Rims		
23.00	23	6600
24 Inch Rims		
7.20	24	1500
7.50	24	1600
8.30	24	2200
9.00	24	2200
9.50 x 9	24	2400
10.00	24	3000
10.00R TG	24	3000
11.00	24	3200
11.20 x 10	24	3200
11.50	24	3400
12.00	24	3400
12.00 x 8.00	24	3400

NOT TO BE USED IN VEHICLES THAT EXCEED 50 M.P.H. (80 K.P.H). / A NE PAS APPLIQUER SUR DES VEHICULES ROULANT A PLUS DE 80 KPH SUR LA ROUTE
NO SER UTILIZADO EN VEHICULOS EN LA CARRETERA QUE SOBREPASAN 80 KPH. / NON UTILIZZARE SU VEICOLI STRADLI CHE SUPERANO I 80 KPH.
NAO DEVE SER USADO EM VEICULOS DE ESTRADA QUE EXCEDAM OS 80 KPH.

OKO_Offroad_01.indd 4 20/04/2010 09:29

Puncture free ANTI-PUNCTURE SEALANT

OKO©

Application chart / Tableau Des Doses D'application
Tabla De Aplication / Tabella di Applicazione / Quadro de Aplicaco

Off Road Vehicles

Industrial, Construction, Agricultural, Tractors, Trailers, Heavy Earthmovers.
Vehicules Industriels, Agricoles, Tracteurs, Semi Remorques, Engines de Terrassment.
Industria, Agricultura, Construccion y Servicios, Tractores, Movimiento de Tierras.
Industriale, Agricolo, Trattori, Edile e Utilita, Veicolo Movimento Terra.
Industria Mineira, Agricola, Tractores, Construcao e Acessorios.

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
24 Inch Rims		
12.00 x 10.00	24	3400
12.00 R. TG	24	3400
12.40	24	3600
13.00	24	3800
13.60	24	3800
14.00	24	4000
14.00 x 8.00	24	4000
14.00 x 10.00	24	4000
14.00 R. RG	24	4000
14.90/13.	24	4400
15.00	24	4600
15.50	24	4800
16	24	5000
16.00 R. TG	24	5000
16.5	24	5200
16.50 / 80	24	5400
16.50 / 85	24	5400
16.90 R.	24	5600
17.50	24	5800
18.00	24	6000
18.40	24	6200
19.40	24	6400
19.50	24	6400
21.00	24	6600
22.00	24	6800
320 / 70	24	3600
360 / 70	24	4200
380 / 70	24	4600
420 / 70	24	5400
24.00	24	7000
26 Inch Rims		
12.4	26	3800
13.6	26	4200
14.90	26	4600
14.90 R	26	4600
15.00	26	5000
16.90	26	5800
16.90 R	26	5800
26 Inch Rims		
18.00	26	6200
18.40	26	6500
18.40 R	26	6500
23.10	26	8000
28.00	26	9400
28.10	26	9600
480 / 70	26	6800
620 / 75	26	8000
26.5 Inch Rims		
600 / 55	26.5	8400
28 Inch Rims		
8.30	28	2500
9.50	28	3000
11.20 / 78	28	3400
11.25	28	3600
12.40 / 78	28	3800
13.00	28	4000
13.60 / 78	28	4200
13.60 R	28	4400
14.00	28	4600
14.90 / 78	28	4800
15.00	28	5200
16.50 / 85	28	5400
16.90 / 14	28	5800
17.00	28	6200
18.40	28	6600
320 / 70	28	4000
360 / 70	28	4600
380 / 70	28	5000
420 / 70	28	5600
480 / 70	28	7000
540 / 65	28	8000
29 Inch Rims		
21.00	29	7800
24.00	29	9000
24.00 R	29	9000
26.50	29	10500
26.50 R	29	10500
29.50	29	12000
29.50 R	29	12000
30.00 / 65	29	12600
32.25 R	29	13000
33.25 R	29	13000
30 Inch Rims		
4.00	30	1400
6.00	30	1600
6.30	30	1800
7.20	30	2400
9.50	30	3000
14.90	30	5200
14.90 R	30	5200
16.90	30	6200
16.90 R	30	6200
17.00	30	6400
18.4	30	7000
21.00	30	8000
21.00 / 80	30	8000
23.1	30	8600
420 / 70	30	6200
480 / 70	30	7600
520 / 70	30	8000
540 / 65	30	8200
30.5 Inch Rims		
600 / 65	30.5	9000
32 Inch Rims		
8.30	32	2800
9.50	32	3200
12.40	32	4000
24.50	32	9600
30.00	32	13600
30.50	32	13600
>>>>> cont'd		

NOT TO BE USED IN VEHICLES THAT EXCEED 50 M.P.H. (80 K.P.H). / A NE PAS APPLIQUER SUR DES VEHICULES ROULANT A PLUS DE 80 KPH SUR LA ROUTE
NO SER UTILIZADO EN VEHICULOS EN LA CARRETERA QUE SOBREPASAN 80 KPH. / NON UTILIZZARE SU VEICOLI STRADLI CHE SUPERANO I 80 KPH.
NAO DEVE SER USADO EM VEICULOS DE ESTRADA QUE EXCEDAM OS 80 KPH.

OKO_Offroad_01.indd 5 20/04/2010 09:29

Puncture free ANTI-PUNCTURE SEALANT

OKO©

Application chart / Tableau Des Doses D'application
Tabla De Aplication / Tabella di Applicazione / Quadro de Aplicaco

Off Road Vehicles

Ride ON Lawn Mowers, Golf Carts, Trailers, Fork Lift Trucks.
Brouettes, Chariots de Golfe, Remorques, Les Tondeuses Autoportees
Segadores Motorizadas, Carros de Golfe, Remolques, Otros.
Tabliaerba, Rimorchi, Altro, "Golf Cart"
Cortadores de Relva, Carrinhos de Golfe, Reboques.

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
33 Inch Rims		
18.00	33	8000
18.00 R	33	8000
27.00	33	13000
27.00 R	33	14000
30.00	33	14000
30.00	33	15000
30.00 x 65 R	33	15000
33.50	33	15000
33.65 R	33	15000
35.00 / 65	33	15800
37.50	33	17000
37.50 R	33	17000
34 Inch Rims		
11.20	34	4400
14.00	34	5600
16.90 / 78	34	6600
18.40	34	8200
18.50	34	8500
20.80 R	34	9000
23.10 R	34	10000
480 / 70	34	8600
520 / 70	34	9000
710 /70	34	11000
35 Inch Rims		
21.00	35	9200
21.00 R	35	9200
24.00	35	10600
24.00 R	35	10600
29.50	35	15000
29.50 R	35	15000
33.25	35	16000
33.25 R	35	16000
37.25	35	18000
36 Inch Rims		
4.00	36	1800
6.50	36	2000
7.20	36	2800
8.30	36	3200
9.50	36	3600
11.20	36	4000
12.40	36	4400
13.60 / 78	36	5600
13.90	36	5800
38 Inch Rims		
4.00	38	1800
8.30	38	3400
9.50	38	4000
11.20	38	4200
12.40	38	4600
13.60	38	5800
13.60 R	38	5800
14.00	38	6000
14.90	38	6000
15.50	38	6400
16.00	38	6600
480 / 70	38	9000
520 / 70	38	9400
580 / 70	38	11000
650 / 65	38	12000
750 / 65	38	14000
16.90/78	38	7000
16.90 R	38	7000
18.00	38	8600
18.40 /78	38	8600
20.80	38	9400
20.80 R	38	9400
39 Inch Rims		
33.50	39	18000
33.50 R	39	18000
37.50	39	20000
37.50 R	39	20000
40.00 / 65	39	20000
40.50	39	22000
40.50 / 75	39	22000
45.00 / 65	39	24000
40 Inch Rims		
7.20	40	3500
42 Inch Rims		
8.30	42	3800
9.50	42	4000
12.40	42	5000
16.90	42	7400
18.40	42	9000
18.40 R	42	9000
20.80	42	10400
20.80 R	42	10400
620 / 70	42	12000
650 / 65	42	12600
43 Inch Rims		
24.00	43	12000
44 Inch Rims		
8.30	44	3800
9.50	44	4400
45 Inch Rims		
45.00	45	25000
46 Inch Rims		
12.40	46	5600
14.90 R	46	7600
18.40 R	46	10000
48 Inch Rims		
9.50	48	5000
49 Inch Rims		
18.00 R	49	11000
21.00	49	12000
24.00	49	14000
27.00	49	15000
31.00 / 80	49	17000
50 Inch Rims		
17.00	50	10000
20.00	50	12000
>>>>> cont'd		

NOT TO BE USED IN VEHICLES THAT EXCEED 50 M.P.H. (80 K.P.H). / A NE PAS APPLIQUER SUR DES VEHICULES ROULANT A PLUS DE 80 KPH SUR LA ROUTE
NO SER UTILIZADO EN VEHICULOS EN LA CARRETERA QUE SOBREPASAN 80 KPH. / NON UTILIZZARE SU VEICOLI STRADLI CHE SUPERANO I 80 KPH.
NAO DEVE SER USADO EM VEICULOS DE ESTRADA QUE EXCEDAM OS 80 KPH.

OKO_Offroad_01.indd 6 20/04/2010 09:29

Puncture free ANTI-PUNCTURE SEALANT

Application chart / Tableau Des Doses D'application
Tabla De Aplication / Tabella di Applicazione / Quadro de Aplicaco

Off Road Vehicles + Refuse Trucks & Skip Lorries

Industrial, Construction, Agricultural, Tractors, Trailers, Heavy Earthmovers.
Vehicules Industriels, Agricoles, Tracteurs, Semi Remorques, Engines de Terrassment.
Industria, Agricultura, Construccion y Servicios, Tractores, Movimiento de Tierras.
Industriale, Agricolo, Trattori, Edile e Utilita, Veicolo Movimento Terra.
Industria Mineira, Agricola, Tractores, Construcao e Acessorios.

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
51 Inch Rims		
24.00	51	15000
27.00	51	16000
30.00	51	18000
33.00	51	21000
36.00	51	22000
37.50	51	24000
37.50 R	51	24000
50.00	51	31000
55.00	51	36000
65.00	51	45000
56.5 Inch Rims		
27.00	56.5	18000
30.00	56.5	20000
57 Inch Rims		
37.00 R	57	26000
40.00	57	30000
50.00 / 90	57	40000
59.5 Inch Rims		
33.00	59.5	25000
36.00	59.5	27000
39.00	59.5	32000

Applies Only To Heavy Vehicles Of 5 Tonnes And Over

> > > > > > > > >

(+ Plus 5t);
(De Mas De 5 Toneladas);
(Di Oltre 5 Tonnellate);
(Acima De 5 Toneladas).

Refuse Trucks & Skip Lorries

Voitures D'eboueurs, Vehicules Utilitaires Sur La Route Normale

Camions De Descechos Y Camiones Volquetes

Camion Per Il Transporto E La Gestione De Rifiuti

Camioes De Recolha De Lixo E Basculantes

Refuse Trucks, Rubbish Carts and Skip Lorries can be fitted normally with the the ON ROAD OKO.

These vehicles can also be fitted with the OFF Road OKO but if so, the should not exceed 50mph (80) kph.

REFER to the WEB SITE of The OKO Group for the extensive lists and updated information - www.oko.com

TYRE Size. / Taille du Pneu / Tamano del neumatico / Dim. Pneumatico / Tomanho do Pneu	RIM / Jante / Llanta	OKO MLS
15 Inch Rims		
12.00	15	400
17 Inch Rims		
10.00	17	500
18 Inch Rims		
10.50	18	700
12.50	18	800
19.5 Inch Rims		
10.00	19.5	1000
19.5R	19.5	2400
20 Inch Rims		
10.00	20	1400
13.00	20	2300
22 Inch Rims		
11	22	2400
22.5 Inch Rims		
11	22.5	2400
24 Inch Rims		
10.00	24	2200
14.00	24	3200

NOT TO BE USED IN VEHICLES THAT EXCEED 50 M.P.H. (80 K.P.H). / A NE PAS APPLIQUER SUR DES VEHICULES ROULANT A PLUS DE 80 KPH SUR LA ROUTE
NO SER UTILIZADO EN VEHICULOS EN LA CARRETERA QUE SOBREPASAN 80 KPH. / NON UTILIZZARE SU VEICOLI STRADLI CHE SUPERANO I 80 KPH.
NAO DEVE SER USADO EM VEICULOS DE ESTRADA QUE EXCEDAM OS 80 KPH.

OKO_Offroad_01.indd 7 20/04/2010 09:29