Parts Page Reorder No. PD11•38
Effective November, 2011
Supersedes PD07•32

3" Dia. Vacuum Disc Sander

Right Angle, .4 hp, Rear Exhaust

Safety, Operation and Maintenance – Save This Document and Educate All Personnel

Trimmed Shroud Models

Model	RPM	Vacuuum	Port Size	Pad Size
50210	15,000	Self-Generated	1" Outer Dia.	3" (80 mm) Dia.
50211	15,000	Central Vacuum	1-1/4" Outer Dia.	3" (80 mm) Dia.

Standard Shroud Models

Model	RPM	Vacuuum	Port Size	Pad Size
50570	15,000	Self-Generated	1" Outer Dia.	3" (80 mm) Dia.
50561	15,000	Central Vacuum	1-1/4" Outer Dia.	3" (80 mm) Dia.

DYNABRADE LIFETIME WARRANTY MADE IN USA

Find The Most Current Offering of Support Documents and Accessories at www.Dynabrade.com

⚠ WARNING

Read and understand this tool manual before operating your air tool. Follow all safety rules for the protection of operating personnel as well as adjacent areas. Always operate, inspect and maintain this tool in accordance with the American National Standards Institute (ANSI) Safety Code for Portable Air Tools – B186.1. For additional safety information, refer to Safety Requirements for the Use, Care and Protection of Abrasive Wheels – ANSI B7.1, Code of Federal Regulation – CFR 29 Part 1910, European Committee for Standards (EN) Hand Held Non-Electric Power Tools – Safety Requirements and applicable State and Local Regulations.



Read and understand tool manual before work starts to reduce risk of injury to operator, visitors, and tool.



Eye protection must be worn at all times, eye protection to conform to ANSI Z87.1.



Ear protection to be worn when exposure to sound, exceeds the limits of applicable Federal, State or local statues, ordinances and/or regulations.



Practice safety requirements. Work alert, have proper attire, and do not operate tools under the influence of alcohol or drugs.



Respiratory protection to be used when exposed to contaminants that exceed the applicable threshold limit values required by law.



Air line hazard, pressurized supply lines and flexible hoses can cause serious injury. Do not use damaged, frayed or deteriorated air hoses and fittings.

Some dust created by sanding, grinding, drilling, and other construction activities contain chemicals known to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- Lead from lead-based paints
- Crystalline silica from bricks and cement and other masonry products
- Arsenic and chromium from chemically treated lumber

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

SAFETY INSTRUCTIONS



Carefully Read and Understand the General and Sander/Polisher sections found in Tool Safety and Operating Guidelines (PN00001676) Before Handling or Using Tool.

Carefully Read all instructions before operating or servicing any Dynabrade® Abrasive Power Tool. Products offered by Dynabrade are not to be modified, converted or otherwise altered from the original design.

Tool Intent: Vacuum Disc Sanders are ideal for deburring, deflashing, surface preparation, cleaning and finishing using proper accessories.

DO NOT USE Tool for Anything Other Than Its Intended Applications.

Training: Proper care, maintenance, and storage of your air tool will maximize tools performance and reduce chance for accident.

Employer's Responsibility: Provide operators with safety instructions and training for safe use of tools and accessories.

Report to Your Supervisor any Condition of the Tool, Accessories or Operation you Consider Unsafe.

MAINTENANCE INSTRUCTIONS

Important: To keep tool safe, a Preventative Maintenance Program is recommended. The program should included inspection of the tool and all related accessories and consumables, including air lines, pressure regulators, filters, oilers, etc. refer to ANSI B186.1 for additional maintenance information. If accessory or tool breakage occurs, investigate failure to determine the cause and correct before issuing tool for work. Use the following schedule as a starting point in developing a Preventative Maintenance Program. If tool does not operate properly (RPM, Vibration, Start/Stop) after these scheduled checks or at any time, the tool must be repaired and corrected before returning tool to use.

INSTALLATION

- To ensure long life and dependable service, use a Closed Loop Air System and Filter-Regulator-Lubricator as diagramed below.
- Each tool should have its own dedicated hose connected to an air supply manifold. Quick disconnects should be installed at the manifold in an effort to reduce contamination into the tool.
- It is strongly recommended that all Dynabrade rotary vane air tools be used with a Filter-Regulator-Lubricator to minimize the possibility of misuse due to unclean air, wet air or insufficient lubrication. Dynabrade recommends the following: **10681** Air Line Filter-Regulator-Lubricator — Provides accurate air pressure regulation, two-stage filtration of water contaminants and micro-mist lubrication of pneumatic components.
- Dynabrade recommends one drop of air lube per minute for each 20 SCFM (example: if the tool specification states 40 SCFM, set the drip rate on the filter-lubricator to 2 drops per minute) Dynabrade Air Lube (P/N **95842**: 1pt/473ml) is recommended.

MAINTENANCE SCHEDULE

Daily (every 8 hours):

- Inspect tool and accessories for damage or broken parts. Replace items as necessary to ensure proper operation and safety.
- Lubricate motor as recommended. Use Dynabrade Air Lube (P/N **95842**: 1pt/473ml) 10W/NR. (1 Drop per minute of air lube per 20 SCFM.)
- Check air line pressure with a gage. (MAX. 90 PSIG or 6.2 Bar operating pressure at the air inlet of the tool.)
- Right angled gear and wick system through gear case grease fitting with 3 plunges of gear oil (P/N **95848**) and grease gun (P/N **95541**). (Prime grease gun prior to greasing.)
- Check tool for proper operation: If operating improperly or demonstrates unusual vibration, the tool must be serviced and problem corrected before further use.

Every 20 Hours or Once a Week Which Ever Comes First:

- Check free speed of tool without the abrasive accessory mounted. Measure RPM (speed) with tachometer and with air pressure set at 90 PSIG while the tool is running. If a governed tool is operating at a higher speed than the RPM marked on the tool housing, the tool must be serviced and corrected before use. A non-governed tool may exceed the RPM marked on the tool by 10% when operated at free speed with no accessories.
- If tool is running fast look for worn, damaged or missing governors, air control rings and silencers. Special care must be taken when servicing governors and speed control devices. Injection molded governor assemblies are non-serviceable and must be replaced.
- If tool is running slow look for clogged inlet screen, air stream, silencer(s) or a malfunctioning governor (see concerns for servicing governors). Service as required.

Every 50 Hours:

- Lubricate planetary gears through gear case grease fitting with 3 plunges of grease (P/N **95542**) and grease gun (P/N **95541**). (Prime grease gun prior to greasing.)

REPAIR

- Use only genuine Dynabrade replacement parts to ensure quality. To order replacement parts, specify Model#, Serial# and RPM of your air tool.
- Mineral spirits are recommended when cleaning the tool and parts. Do not clean tool or parts with any solvents or oils containing acids, esters, ketones, chlorinated hydrocarbons or nitro carbons.
- DO NOT clean or maintain tools with chemicals that have a low flash point (example: WD-40®).
- Motor Tune-Up Kit are available (when applicable) which includes high wear and medium wear motor parts.
- Air tool markings must be kept legible at all times, if not, reorder housing and replace. User is responsible for maintaining specification information.
- After maintenance is performed on tool, add a few drops of Dynabrade Air Lube (P/N **95842**) to the tool inlet and start the tool a few times to lubricate air motor. Verify RPM (per 20 hr maintenance schedule), vibration and operation.

HANDLING & STORAGE

- Use of tool rests, hangers and/or balancers is recommended.
- Protect tool inlet from debris (see Notice).
- DO NOT carry tool by air hose or near the tool throttle lever.
- Store accessories in protective racks or compartments to prevent damage.
- Follow the handling instructions outlined in the operating instructions when carrying the tool and when changing accessories.
- Protect accessories from exposure to water, solvents, high humidity, freezing temperature and extreme temperature changes.

END OF USE/DISPOSAL


When tool has reached its end of useful service, disassemble tool into its primary components (i.e. steel, aluminum and plastic part) and recycle or discard per local, state and/or federal regulations as to not harm the environment.

NOTICE

All Dynabrade motors use the highest quality parts and metals available and are machined to exacting tolerances. The failure of quality pneumatic motors can most often be traced to an unclean air supply or the lack of lubrication. Air pressure easily forces dirt or water contained in the air supply into motor bearings causing early failure. It often scores the cylinder walls and the rotor blades resulting in limited efficiency and power. Our warranty obligation is contingent upon proper use of our tools and cannot apply to equipment which has been subjected to misuse such as unclean air, wet air or a lack of lubrication during the use of this tool.

AIR SYSTEM

Closed Loop Pipe System, Sloped in Direction of Air Flow




- Dynabrade Air Power Tools are designed to operate at 90 PSIG (6.2 Bar) maximum air pressure at the tool inlet, when the tool is running. Use recommended regulator to control air pressure.
- Ideally the air supply should be free from moisture. To facilitate removing moisture from air supply, the installation of a refrigerated air dryer after the compressor and the use of drain valves at each tool station is recommended.

Models:
50210, 50211, 50561, 50570

3" Dia. Vacuum Disc Sander
Complete Assembly

Index Key

No.	Part #	Description
1	**51346**	Pad
2	**50771**	Shroud - Standard
	50789	Shroud - Trimmed
3	**97326**	Clamp
4	**02029**	Spindle
5	**02035**	Lock Nut
6	**01486**	Felt Silencer
7	**54520**	Bearing
8	**97116**	Shim - .001" (0.03 mm)
9	**97117**	Shim - .002" (0.05 mm)
10	**97118**	Shim - .003" (0.08 mm)
11	**02597**	Gear
12	**02044**	Wick
13	**02045**	Wick
14	**02031**	Housing (Includes: **01041**, **02041**)
15	**01041**	Gear Oil Fitting
16	**02041**	Gear Oil Plate
17	**02033**	Needle Bearing
18	**02598**	Pinion
19	**01461**	Lock Nut
20	**02649**	Bearing
21	**54543**	Shim - .001" (0.03 mm
22	**54544**	Shim - .002" (0.05 mm)
23	**54551**	Shim - .003" (0.08 mm)
24	**01478**	Front Bearing Plate
25	**50767**	Pin (2)
26	**01479**	Spacer
27	**02037**	Rotor
28	**01480**	Vane (4/pkg.)
29	**01476**	Cylinder
30	**02676**	Rear Bearing Plate
31	**02696**	Bearing
32	**02679**	Shield
33	**01547**	Collar
34	**Housing**	
	50774	Model: 50210
	50775	Model: 50211
	50773	Model: 50561
	50772	Model: 50570
35	**01469**	Speed Regulator Assy. (Includes: **01024**, **95730**)
36	**01024**	O-Ring
37	**95730**	O-Ring
38	**01464**	Seal
39	**01472**	Tip Valve
40	**01468**	Spring
41	**01564**	Air Control Ring
42	**95558**	Retaining Ring
43	**01449**	Valve Stem
44	**01448**	Throttle Lever
	01462	Safety-Lock Lever (Optional)
45	**12132**	Pin
46	**96584**	Vac. Hose – Self-Gen. (Non-Conductive/Grey)
	31937	Vac. Hose – Cnt. Vacuum (Conductive/Black)
47	**95711**	Retaining Ring
48	**95438**	O-Ring
49	**94532**	Vacuum Adapter
50	**95375**	O-Ring
51	**94526**	Spacer
52	**94523**	Inlet Adapter
53	**53207**	Vacuum Assembly
54	**94521**	Muffler Base
55	**94528**	Silencer
56	**02295**	Muffler Cap (Inc.'s **31953**)
57	**31953**	Wire
58	**02292**	Muffler Cap & Ball Swivel Assy.
59	**31908**	Hose Cuff – Cnt. Vacuum (Conductive/Black)
	95601	Hose Cuff – Self-Gen. (Non-Conductive/Grey)
60	**97180**	Hose Cuff – Cnt. Vacuum (Conductive/Black)



95262 14mm Wrench

KEY

- **O** Oil: **O_1 = Air Lube**
- **W** Wicking: **W_1 = Gear Oil**
- **A** Adhesive: **A_4 = Loctite #680**, **A_8 = Loctite #567**, **A_{10} = Loctite #243**
- **T** Torque: **N•m x 8.85 = In. - lbs.**

LIFETIME WARRANTY

To validate Dynabrade Lifetime Warranty, you must register each tool at: www.dynabrade.com. Registration of each tool at website is required. Dynabrade will not honor Lifetime Warranty on unregistered tools. Please view the entire Lifetime Warranty Policy at : www.dynabrade.com.

MACHINE SPECIFICATIONS

Model	Speed	Power	Sound	Air Consumption	Spindle	Weight	Length	Height
50210	15,000 RPM	.4 hp (298 W)	89 db(A)	21 SCFM (595 LPM)	1/4"-20 Male	1.7 lb. (0.7 kg)	9.69" (246 mm)	3.86" (98 mm)
50211	15,000 RPM	.4 hp (298 W)	86 db(A)	21 SCFM (595 LPM)	1/4"-20 Male	1.7 lb. (0.7 kg)	10" (254 mm)	3.86" (98 mm)
50561	15,000 RPM	.4 hp (298 W)	86 db(A)	21 SCFM (595 LPM)	1/4"-20 Male	1.7 lb. (0.7 kg)	10" (254 mm)	4.38" (111 mm)
50570	15,000 RPM	.4 hp (298 W)	89 db(A)	21 SCFM (595 LPM)	1/4"-20 Male	1.7 lb. (0.7 kg)	9.69" (246 mm)	4.38" (111 mm)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. 1/4" (6 mm)
Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744

OPTIONAL ACCESSORIES



Motor Tune-Up Kit
- Includes assorted parts to help maintain and repair motor.

Part No. 96179



Drop-In Motor
- Allows quick and easy replacement. No motor adjustments needed.

Part No. 02050



Dynaswivel®
- Swivels 360° at two locations which allows an air hose to drop straight to the floor, no matter how the tool is held.

Part No. 94300 – 1/4" NPT.




Dynabrade Air Lube
- Formulated for pneumatic equipment.
- Absorbs up to 10% of its weight in water.
- Prevents rust and formation of sludge.
- Keeps pneumatic tools operating longer with greater power and less down time.

Part No. 95842: 1pt. (473 ml)
Part No. 95843: 1gal. (3.8 L)




Portable Vacuum Systems
- Dynabrade offers a wide assortment of vacuuming options to choose from. To help make your selection please request the most current portable vacuum systems literature form your local representative or by searching our web site.


SHROUD CONFIGURATIONS – SIDE VIEW



UNALTERED SHROUD



ALTERED SHROUD



REFERENCE CONTACT INFORMATION

1. **American National Standards Institute – ANSI**
   1899 L Street, NW
   11th Floor
   Washington, DC 20036
   Tel: 1 (212) 642-4900

2. **Government Printing Office – GPO**
   Superintendent of Documents
   Attn. New Orders
   P.O. Box 371954
   Pittsburgh, PA 15250-7954
   Tel: 1 (202) 512-1803

3. **Power Tool Institute, Inc.**
   P.O. Box 818
   Yachata, Oregon 97498-0818
   Tel: 1 (503) 547-3185

4. **European Committee for Standardization**
   Rue de Stassart 36
   B - 1050 Brussels, Belgium

DYNABRADE, INC. ***www.dynabrade.com***

8989 Sheridan Drive • Clarence, NY 14031-1419 • Phone: (716) 631-0100 • Fax: 716-631-2073 • International Fax: 716-631-2524

©DYNABRADE, INC., 2011
PRINTED IN USA PD11.38_11/11